LD INTELLECTUAL PROPERTY ORGANIZATION International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7: H04N 5/225, 5/76, 5/262, G03B 17/48, 17/24, G06K 9/00, 9/54, 9/60

A1

(11) International Publication Number:

WO 00/51342

(43) International Publication Date:

31 August 2000 (31.08.00)

(21) International Application Number:

PCT/US00/05029

(22) International Filing Date:

28 February 2000 (28.02.00)

(30) Priority Data:

09/258,813

26 February 1999 (26.02.99) US

- (71) Applicant: SONY ELECTRONICS, INC. [US/US]; 1 Sony Drive, Park Ridge, NJ 07656 (US).
- (72) Inventors: ABRAM, Philip, Michael; 8 Black Walnut Drive, Warwick, NY 10990 (US). SATO, Robert, J.; 2077 Center Avenue #17D, Fort Lee, NJ 07024 (US).
- (74) Agents: GARRETT, Arthur, S. et al.; Finnegan, Henderson, Farabow, Garrett & Dunner, L.L.P., 1300 I Street, N.W., Washington, DC 20005-3315 (US).


(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published

With international search report.

Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

(54) Title: METHODS AND APPARATUS FOR ASSOCIATING DESCRIPTIVE DATA WITH DIGITAL IMAGE FILES



(57) Abstract

Methods and system consistent with the present invention provide means for labeling (140) digital image data (130) generated by digital imaging devices (100), such as digital cameras and camcorders, with descriptive information. In one embodiment, a menu of descriptive terms (520) is displayed to the user of the digital imaging device. The user chooses one or more of the descriptive terms (530) and the user's choices are associated with the digital image. The descriptive terms may be used, for example, to generate a file name or may be later displayed with the digital image.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	A Ibania	ES	Spain	• •	_
AM	Armenia	FI	Finland	LS	Lesotho
AΤ	Austria	FR	France	LT	Lithuania
AU	Australia	GA	Gabon	LU	Luxembourg
AZ	Azerbaijan	GB		LV	Latvia
BA	Bosnia and Herzegovina	GE	United Kingdom	MC	Monaco
BB	Barbados	GH	Georgia	MD	Republic of Moldova
BE	Belgium	GN	Ghana	MG	Madagascar
BF	Burkina Faso	GR	Guinea	MK	The former Yugoslav
BG	Bulgaria		Greece		Republic of Macedoni
BJ	Benin	HU	Hungary	ML	Mali
BR	Brazil	IE	Ireland	MN	Mongolia
BY	Belarus	IL	Israel	MR	Mauritania
CA	Canada	IS	Iceland	MW	Malawi
CF		IT	Italy	MX	Mexico
CG	Central African Republic	JP	Japan	NE	Niger
CH	Congo	KE	Kenya	NL	Netherlands
CI	Switzerland	KG	Kyrgyzstan	NO	Norway
	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand
CM	Cameroon		Republic of Korea	PL	Poland
CN	China	KR	Republic of Korea	PT	Portugal
CU	Cuba	KZ	Kazakstan	RO	Romania
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation
DE	Germany	LI	Liechtenstein	SD	Sudan
DK	Denmark	LK	Sri Lanka	SE	Sweden
EE	Estonia	LR	Liberia		
		LK	Liocha	SG	Singapore

SN	Senegal
SZ	Swazitand
TD	Chad
TG	Togo
TJ	Tajikistan
TM	Turkmenistan
TR	Turkey
TT	Trinidad and Tobago
UA	Ukraine
UG	Uganda
US	United States of Americ
ŲΖ	Uzbekistan
VN	Viet Nam
YU	Yugoslavia
ZW	Zimbabwe

Slovenia

Slovakia

SI

SK

10

15

20

25

30

METHODS AND APPARATUS FOR ASSOCIATING DESCRIPTIVE DATA WITH DIGITAL IMAGE FILES

BACKGROUND OF THE INVENTION

The present invention relates generally to methods and apparatus for improving digital image processing.

Digital imaging devices, such as digital cameras and scanners, create digital representations of images and store the digital representations to data files for future use and manipulation. Data file names are created either automatically or entered in manually by the user. Conventional digital imaging devices that create filenames automatically typically use consecutive alphanumeric filenames, such as "xxx0001.jpg" and "xxx0002.jpg", to label the data files. While the files are labeled automatically, the file name created by the device has no relevance to the contents or description of the image. Nondescriptive filenames make organizing, indexing, sorting and retrieval of these files difficult and time consuming.

Some conventional imaging devices allow the use of descriptive file names, but these file names must be entered by the user. In conventional scanning devices, for example, pages to be scanned are loaded into a document feeder. The user specifies scan settings, including a file name for the stored image. The user must enter a descriptive name, such as "capecod1." When the user indicates that the desired settings are chosen by, for example, pressing a button, the scanned image is then saved as the indicated file name.

Some conventional digital cameras create a file name for the image file using data from an internal clock that is used also for automatic time stamping. These conventional devices may create, for example, an alphanumeric file name for a standard JPEG file of 050198182350.JPG for an image created on May 1, 1998 at 6:23pm 50 seconds. The date and time information may also be integrated with the digital image information. This information is useful for retrieving an image based on date and time of

10

15

20

25

creation. Conventional automatic digital imaging devices, however, do not stamp a digital image recording with other information useful for recalling an image, such as the location of the capture or the event associated with the image, such as a picnic, birthday or other event.

Some commercially available digital cameras are combined with global positioning system (GPS) receivers that collect and store position data describing the position of the camera at the time it acquired an image. These cameras, however, simply stamp the image data with the latitudinal and longitudinal coordinates which do not allow for easy recognition by others of the location where the image was acquired. They do not, for example, translate the coordinates into easily recognizable place names like "Cape Cod."

SUMMARY OF THE INVENTION

Methods, systems, and articles for manufacture consistent with the present invention overcome the shortcomings of existing systems by providing methods and means for labeling digital image data. According to one aspect of the invention, a digital image is acquired using a digital imaging device. A menu of descriptive terms is displayed to a user and the user selects at least one of the descriptive terms for association with the digital image file. In another aspect of the invention, an audio input device provides the digital imaging device with an audio signal containing at least one descriptive term. The descriptive term in the audio signal is associated with the digital image data file. In yet another aspect of the invention, a location determination device provides the digital imaging device with location information representing a geographic location where the digital image was acquired. The location information is associated with the digital image data file.

• 5

10

15

20

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are incorporated in and constitute a part of this specification, illustrate the invention and, together with the description, serve to explain the principles of the invention.

- Fig. 1 is a block diagram of a digital camera consistent with the present invention;
- Fig. 2 is a block diagram of a digital camera with audio receiver consistent with the present invention;
- Fig. 3 is a block diagram of a digital camera with location determination unit consistent with the present invention;
 - Fig. 4 is a flow diagram illustrating a method consistent with the present invention;
 - Fig. 5 is a diagram of a digital camera consistent with the present invention;
- Fig. 6 is a diagram of a digital camera consistent with the present invention;
 - Fig. 7 is a flow diagram of a method of associating audio data with a digital image file consistent with the present invention;
 - Fig. 8 shows a diagram of a digital camera consistent with the present invention; and
 - Fig. 9 is a flow diagram of a method of associating location information data with a digital image file consistent with the present invention.

DETAILED DESCRIPTION

Reference will now be made in detail to an implementation
consistent with the principles of the present invention as illustrated in the accompanying drawings. Wherever possible, the same reference numbers will be used throughout the drawings and the following description to refer to the same or like parts.

10

15

20

25

30

A. <u>Introduction</u>

Methods, systems, and articles of manufacture consistent with the present invention assist a user in archiving, indexing, sorting and retrieval stored image files by associating information relevant to the digital image with the image data file. In a digital imaging device equipped with an audio receiver, the user records audio information describing the digital image that is acquired. The descriptive audio information is converted to digital information that is used to label the image. The digitized descriptive information may be used, for example, to create a descriptive file name or print information on the image.

In an alternative embodiment, a digital imaging device is equipped with a location determination unit that provides location information to the digital imaging device. The location information may be converted to geographic coordinates, which may in turn be used to determine a place name or other descriptive term. The geographic coordinates, place name, or descriptive term may be used, for example, to create a descriptive file name or print information on the image.

B. <u>Digital Cameras</u>

Fig. 1 illustrates a system 100 consistent with the present invention. Digital camera 100 may be, for example, a digital still camera or a digital video camera. As shown in Fig. 1, digital camera 100 comprises a lens 110, a charge coupled device (CCD) 120, an analog-to-digital converter 130, a display 135, and a processor 140. Lens 110 is an optical lens formed of glass or plastic that focuses light on the surface of light-sensitive CCD 120. CCD 120 generates an electrical signal in accordance with an image provided by lens 110 and provides the electrical signal to analog-to-digital converter 130. Analog-to-digital converter 130 converts the analog image signal into digital information, which can be used to reproduce the acquired image, and transmits the digital information to processor 140.

Processor 140 may be any commonly available digital processor special purpose digital processor. Processor 140 may also store the image in a memory 150. Memory 150 may include any storage device capable of

• 5

10

15

20

25

30

storing data processed by processor 140, including, for example, data base 152. Memory 150 may be, for example, a floppy disk, or other magnetic medium, or a blank RAM. Data base 152 may contain, for example, a dictionary of words, place names, events, or other descriptive terms.

Processor 140 is also connected to at least one user input device 155 via any suitable data connection. User input device 155 can be any device capable of passing information to or receiving data from processor 140. By way of example only, user input device 155 may be a scroll wheel, button, key, or other suitable means of accepting input from a user. Digital camera 100 may also include a display 180, such as a cathode ray tube (CRT) or liquid crystal display (LCD), for displaying information.

Consistent with the present invention, digital camera 100 may also include an audio receiver 265, such as a microphone, as shown in Fig. 2. Audio receiver 265 may be located physically inside camera 100 or externally attached as a peripheral device, such as audio receiver 265. Audio receiver 265 may be operatively connected to an optional recorder 260 or other means of recording audio received from audio receiver 265. In implementations without optional recorder 260, audio may be stored in memory 150.

Fig. 3 is a block diagram of a digital camera 100 with a location determination unit 375. Location determination unit 375 may be external to camera 100 as shown in Fig. 3 or located inside camera 100. Location determination unit 375 tracks the camcorder's location via signals collected by an antenna. Location determination unit 375 may be, for example, a conventional global positioning satellite (GPS) receiver. Location determination unit 375 is capable of outputting information such as time, position, and velocity to camera 100. Location determination unit 375 optionally may comprise or be operatively connected to a memory containing a database of geographic coordinates and familiar places names. Location determination unit 375 may obtain a place name corresponding to the geographic coordinates by, for example, comparing the coordinates to the information in the database and determining the closest location.

10

15

Location determination unit 375 passes the location information (such as the coordinates or place name) to camera control 370. Camera control 370 is operatively connected to processor 140 and passes location information to processor 140. As described above, processor 140 is operatively connected to memory 150 which may contain a database of geographic coordinates and familiar places names. Processor 140 may obtain a place name corresponding to the geographic coordinates by, for example, comparing the coordinates to the information in the database and determining the closest location. Processor 140 may also contain a character generator that produces a bit map of the text information.

C. Methods of Associating Descriptive Data with an Image File

Fig. 4 is a flow chart illustrating a process of associating descriptive data with a digital image file consistent with the present invention. At some point in the process an image is acquired (step 410). After the image is acquired, a menu is displayed to the user (step 420). To display the menu, a user may activate the menu manually by, for example, pushing a button on the camera, or by speaking a command. In another embodiment, the menu is automatically activated by the act of acquiring an image.

Fig. 5 shows a back of an imaging device that is consistent with the present invention. As shown in Fig. 5, display front 510 may contain 20 display area 520 and user input area 540. Display area 520 displays a list of menu items. Menu items may be, for example, descriptive terms, categories of content, relationships, or stored information created by the user. The content of image files may be categorized based on events (such as 25 BIRTHDAY, VACATION, GRADUATION) or relationships of subjects in the images (such as MOM, DAD, SON, FRIEND). User input area 540 may comprise, for example, one or more buttons or scroll wheels for scrolling through the choices until the user's choice is highlighted. User input area 140 also may be digital representations of buttons, keys, or a scroll wheel as displayed, for example, on an LCD display. User input area 140 may also include a means for accepting voice commands, such as a microphone connected to a voice synthesizer.

30

' 5

10

15

20

25

30

In Fig. 5, for example, the user has highlighted the choice, "Holidays." While the menu is displayed to the user, the user indicates one or more of the displayed items by, for example, manipulating a scroll wheel, pushing a button, or speaking a command. If the choice indicated by the user has sub-menus, the list of items in the sub-menu is displayed when the choice is indicated (step 420) and the user must again indicate a choice (step 430). As shown in Fig. 6, for example, once the user has indicated the choice "Holidays," a list of holidays appears in the display.

If the user's choice, as indicated in step 430, does not have submenus, text corresponding to the user's choice is associated with the image data file (step 450). The text may be used, for example, as a descriptive file name, such as "4thofjuly.jpg." If more than one item has been chosen, the file name may become, for example, "VACATION_4thofjuly_070498_jpg." In another embodiment consistent with the present invention, the text may be printed on the image, either in the form as stored (e.g. VACATION_4thofjuly_070498_jpg) or expanded to a more meaningful form, such as "VACATION, Fourth of July, July 4, 1998, 6:23:50 P.M." The descriptive information may be converted to a bit map of characters with appropriate masking information is added to the digital image file. The processor, for example, may composite the "Fourth of July" bit map onto the video image. The resulting composited image will be displayed on the camera viewfinder and/or stored to memory.

Consistent with the present invention, a digital imaging device may also receive information from an audio input device. Fig. 7 is a flow chart illustrating a process of associating descriptive data obtained from an audio receiver with a digital image file. Fig. 8 shows a view of the back of a digital camera 800. Consistent with the present invention, audio information is associated with digital image data. At some point in the process an image is acquired (step 710). Before, during, or after the image is acquired, a user, or subsequent user, receives audio to be associated with the image file (step 720). The audio may be received by, for example, speaking into audio receiver 265 attached to digital camera 100 or audio receiver 810 located in

10

15

20

25

30

digital camera 800. In another exemplary embodiment, the audio is received later, when subsequently processing or recalling the image files, by using a microphone or other audio input device attached to a processing computer. The audio may be received at the time of shooting or added later, when the image file is processed or recalled.

The audio may contain such content as a person commenting on the image he is shooting, for example "David on vacation in Washington D.C." If the audio should be associated with the image file as is (step 724), the audio is linked to the image data (step 726) and may subsequently be recalled and replayed when the digital image file is recalled.

Alternatively, the audio may be converted to a digital audio file (step 730). The digital audio file may be stored and subsequently recalled and replayed when the digital image file is recalled. The digital audio file may also be processed, for example, using voice recognition software either in the digital camera or in any computer that is subsequently processing the image file (step 735). If the voice recognition process results in more than one possible choice (step 740), the choices may be displayed to the user (step 742). The user may indicate a choice by, for example, manipulating a scroll wheel or using buttons, such as those provide in user input areas 540 of Fig. 5 or 640 of Fig. 6.

If the voice recognition process does not recognize words in the digital audio file as words in the chosen language (step 736), the process may proceed with a default process for determining a file name (step 738). If, however, words in the data base are recognized, the process proceeds with step 740. The words may be used as is or, alternatively, compared to a list of words in a data base. For example, the words recognized by the voice recognition software may be compared against a data base of words commonly used to describe images, such as "David, "vacation" and Washington, D.C." either provided by the manufacture as part of the image. The use of a common words data base may prevent the file from being named by other nondescriptive words that the voice recognition software may recognize, such as "in, "the," and "a." Descriptive words may be used to

• 5

10

15

20

25

30

create a file name, such as "DAVID_VACATION_WASHINGTON_DC.jpg," file tag, or overlay for displaying on the image file (such as "David in vacation in Washington, DC"). Once again software in the computer could search the database of image files for a file name with a key word like "David" or "Vacation".

If more than one word in the data base is recognized (step 740), the words are displayed to the user (step 742). In Fig. 8, for example, the voice recognition process resulted in five close matches. User input area 840 may comprise, for example, one or more buttons or scroll wheels for scrolling through the choices until the user's choice is highlighted. User input area 840 also may be digital representations of buttons, keys, or a scroll wheel as displayed, for example, on an LCD display. In Fig. 8, for example, the user has highlighted the choice, ""David on vacation." Once the user has indicated the choice "David on vacation," the user's input is accepted (step 744), and the text corresponding to the user's choice is associated with the image data (step 770). The descriptive label may be used, for example, as a descriptive file name, such as "david_acation.jpg."

In another embodiment consistent with the present invention, the file name is printed inconspicuously on the image, either in the form as stored (e.g. VACATION_4thofjuly_070498_jpg) or expanded to a more meaningful form, such as "VACATION, Fourth of July, July 4, 1998, 6:23:50 P.M." The descriptive information may be converted to a bit map of characters with appropriate masking information is added to the digital containing the descriptive information image file. Masking information is a set of instructions on how to combine the image with the digital image file. The processor, for example, may composite the "Fourth of July" bit map onto the video image. The resulting composited image will be displayed on the camera viewfinder and/or stored to memory.

In yet another embodiment consistent with the present invention, a digital imaging device may also receive information from a location determination device, such as a GPS. Fig. 9 a flow chart illustrating a

10

15

20

25

30

process of associating descriptive data obtained from an location determination device with a digital image file.

Consistent with the present invention, a digital imaging device acquires an image (step 910). The digital imaging device also receives location information from a location determination device, such as a GPS (step 920). The location information received may be, for example, longitudinal and latitudinal coordinates of the location of the camera when the image was acquired. The coordinates may be associated with the file as is (step 924), in which case the coordinates are simply linked to the image data (step 926).

If not associated as is, the location information may be converted to textual location information (step 930). For example, the longitudinal and latitudinal coordinates may be used to obtain a city or location name derived from map data by using a look-up table of names associated with coordinates. The coordinate information may also be used to obtain graphical map information derived from the map data, supplied to the device on, for example, a replaceable memory cartridge.

The location coordinates may be compared, for example, to entries in a location data base stored in memory. The location data base may contain, for example, global location coordinates and alphanumeric place names such as "Orlando, FL" or "Manhattan, NY." If the coordinates do not correspond exactly to any location in the data base (step 936), the process may default (step 938). Alternatively, the process may choose multiple entries with coordinates near the given coordinates (step 940) and display the list of place names to the user (step 942). If the coordinates correspond to more than one place name, such as "Manhattan, NY" and "Radio City Music Hall," or alphanumeric place name, all entries may be displayed to the user. The user then indicates which of the place names should be associated with the particular image file (step 944). The user may, for example, scroll through the choices using a scroll wheel or indicate a choice using buttons on the camera. The alphanumeric place name may be, for example, imprinted on the printed photo, used to generate the file name, as in MANHATTAN.JPEG.

D. <u>Conclusion</u>

The foregoing description of implementations of the invention have been presented for purposes of illustration and description. They are not exhaustive and do not limit the invention to the precise form disclosed.

Modifications and variations are possible in light of the above teachings or may be acquired from practicing of the invention. For example, the described implementation includes software but the present invention may be implemented as a combination of hardware and software or in hardware alone. The invention may be implemented with both object-oriented and non-object-oriented programming systems. The scope of the invention is defined by the claims and their equivalents.

WHAT IS CLAIMED IS:

	1.	A method for labeling digital image data comprising:
		acquiring a digital image (410);
5		displaying a menu of descriptive terms (420);
		receiving an indication from a user selecting at least one
	descriptive to	erm in the menu (430); and
		associating the at least one descriptive term with an image data
	file containin	g the digital image (450).

10

2. The method of claim 1, wherein associating the at least one descriptive term includes:

generating a file name for the image data file based on the at least one descriptive term indicated by the user.

15

3. The method of claim 1, wherein associating the at least one descriptive term includes:

linking the at least one descriptive term with the digital image;

20

25

and

displaying the at least one descriptive term with the digital image, when the digital image is displayed.

4. A method for labeling digital image data comprising: acquiring a digital image (710);

receiving an audio signal containing at least one descriptive term (720);

deriving the at least one descriptive term from the audio signal (736); and

associating the at least one descriptive term with an image data file containing the digital image (770).

• 5

5.	The method of claim 4,	I, wherein associating the at least o	one
descriptive te	erm includes:		

converting the audio signal to a digital audio file; and associating the digital audio file with the image data file containing the digital image.

6. The method of claim 5, wherein associating the digital audio file includes:

linking the digital audio file with the image data file so that the image data file is recalled when the digital audio file is recalled.

7. The method of claim 4, wherein associating the at least one descriptive term includes:

converting the audio signal to a digital audio file;

processing the digital audio file to obtain text comprising at least one word; and

associating the text with the image data file.

8. The method of claim 7, wherein associating the text with the image data file includes:

generating a file name for the image data file based on the text.

- 9. The method of claim 7, wherein associating the text includes: linking the text with the digital image; and
- displaying the text with the digital image, when the digital image is displayed.
 - 10. The method of claim 7, wherein processing the digital audio file includes:
- processing the digital audio file to obtain text comprising at least one candidate word;

comparing the text to a data base of stored words to obtain at least one descriptive word; and

associating the at least one descriptive word with the image data file.

5

11. The method of claim 10, wherein associating the at least one descriptive word with the image data file includes:

generating a file name for the image data file based on the at least one descriptive word.

10

20

25

30

12. The method of claim 10, wherein associating the at least one descriptive word includes:

linking the at least one descriptive word with the digital image; and

displaying the at least one descriptive word with the digital image, when the digital image is displayed.

13. The method of claim 10, wherein associating the at least one descriptive word with the image data file includes:

displaying a menu containing the at least one descriptive word to a user;

receiving an indication from the user selecting at least one descriptive term in the menu; and

associating the at least one selected descriptive term with an image data file containing the digital image.

14. A method for labeling digital image data comprising: acquiring a digital image (910);

generating location information representing a geographic location where the digital image was acquired (930); and

associating the location information with an image data file containing the digital image (970).

15.	The method of claim 14, wherein generating location information
comprises:	

receiving numeric geographic coordinates from a location determination device;

determining at least one alphanumeric location label corresponding to the numeric geographic coordinates; and associating the at least one alphanumeric location label with the image data file.

10 16. The method of claim 14, wherein generating location information comprises:

receiving numeric geographic coordinates from a location determination device;

displaying a menu of at least one alphanumeric location label corresponding to points near the location corresponding to the numeric geographic coordinates; and

receiving an input from a user to select at least one of the at least one alphanumeric location label in the menu.

20 17. The method of claim 15, wherein associating the at least one alphanumeric location label with the image data file includes:

generating a file name for the image data file based on the at least one alphanumeric location label.

25 18. The method of claim 15, wherein associating the at least one alphanumeric location label with the image data file includes:

linking the at least alphanumeric location label with the digital image; and

displaying the at least one alphanumeric location label with the digital image, when the digital image is displayed.

15

19. The method of claim 15, wherein associating the at least one
alphanumeric location label with the image data file includes:
displaying the at least one alphanumeric location label to a user;
receiving an indication from the user selecting at least one
alphanumeric location label in the menu; and
associating the at least one selected alphanumeric location
label with an image data file containing the digital image.

20. An digital imaging device comprising:

10

5

an imager device;

a memory having program instructions, and

a processor configured to use the program instructions to:

acquire a digital image by the imager device;

display a menu of descriptive terms;

15 receive an indication from a user selecting at least one descriptive term in the menu; and

associate the at least one descriptive term with an image data file containing the digital image.

20 21. The device of claim 20, wherein the processor is further configured to:

generate a file name for the image data file based on the at least one descriptive term indicated by the user.

25 22. The device of claim 20, wherein the processor is further configured to:

link the at least one descriptive term with the digital image; and display the at least one descriptive term with the digital image, when the digital image is displayed.

30

A digital imaging device, comprising:a lens system that acquires a digital image;

and

• 5

15

20

	an imager device for converting the image to a digital image
signal;	
	an audio input device that receives an audio signal containing as
least one de	escriptive term and converts the audio signal to a digital audio
signal; and	

a processor for associating the at least one descriptive term with an image data file containing the digital image signal.

24. The device of claim 23, wherein the processor further comprises:

a converter for converting the audio signal to a digital audio file;

a second processor for associating the digital audio file with the image data file containing the digital image.

25. The device of claim 24, wherein the processor further comprises:

a third processor for linking the digital audio file with the image data file so that the image data file is recalled when the digital audio file is recalled.

26. The device of claim 23, wherein the processor further comprises:

a converter for converting the audio signal to a digital audio file;

25 and

a second processor for obtaining text comprising at least one word from the digital audio file; and

a third processor for associating the text with the image data file.

30 27. The device of claim 26, wherein the third processor further comprises:

a fourth processor for generating a file name for the image data file based on the text.

28. The device of claim 26, wherein the third processor further comprises:

a fourth processor for linking the text with the digital image; and a display for displaying the text with the digital image, when the digital image is displayed.

10 29. A digital imaging device, comprising:
a lens system (110) that acquires a digital image;
an imager device (130) for converting the image to a digital image signal;

an audio input device (260) that receives an audio signal containing as least one candidate word and converts the audio signal to a digital audio signal;

a memory (150) for storing a data base of words; and a processor (140) for

comparing the at least one candidate word to the data

20 base of stored words to obtain at least one descriptive word; and
associating the at least one descriptive word with an
image data file containing the digital image signal.

30. The digital imaging device of claim 29, wherein the processor further comprises:

means for generating a file name for the image data file based on the at least one descriptive word.

31. The digital imaging device of claim 29, wherein associating the at least one descriptive word further comprises linking the at least one descriptive word with the digital image and wherein the digital imaging device further comprises:

• 5

10

15

20

25

a display (180) for displaying the at least one descriptive word with the digital image, when the digital image is displayed.

32. The digital imaging device of claim 29, further comprising: a display (180) for displaying the at least one descriptive word with the digital image, when the digital image is displayed;

an user input mechanism (155) for allowing a user to select at least one descriptive word in the menu; and

a second processor (140) for associating the at least one selected descriptive word with an image data file containing the digital image.

33. A digital imaging device, comprising:

a lens system (110) that acquires a digital image;

an imager device (130) for converting the image to a digital image signal;

a location determination device (375) that generates location information representing a geographic location where the digital image was acquired; and

a processor (340) for associating the location information with an image data file containing the digital image signal.

34. A digital imaging device, comprising:
a lens system (110) that acquires a digital image;
an imager device (130) for converting the image to a digital image signal;

a location determination device (375) that generates location information representing a geographic location where the digital image was acquired;

a memory (350) for storing a data base of alphanumeric location 30 labels; and

a processor (340) for

determining at least one alphanumeric location label corresponding to the numeric geographic coordinates; and associating the at least one alphanumeric location label with an image data file containing the digital image signal.

5

- 35. The digital imaging device of claim 34, further comprising: a display (380) for displaying a menu of the at least one alphanumeric location label; and
- a user input mechanism (355) for allowing a user to select at least one of the at least one alphanumeric location labels in the menu.
 - 36. The digital imaging device of claim 34, wherein the location determination device generates a file name for the image data file based the at least one alphanumeric location label.

15

- 37. The digital imaging device of claim 34, further comprising: a second processor for linking the at least one alphanumeric location label with the digital image; and
- a display for displaying the at least one alphanumeric location label with the digital image, when the digital image is displayed.

38.	The digital imaging device of claim 34, further comprising:
	a second processor for associating the at least one selected
alphanu	meric location label with an image data file containing the digital
image.	

• 5

15

- 39. A computer-readable medium containing instructions for controlling a computer system to perform a method, the computer system having a group of data structures reflecting a logical structure of a data source, the method comprising:
- 10 acquiring a digital image;

displaying a menu of descriptive terms;

receiving an indication from a user selecting at least one descriptive term in the menu; and

associating the at least one descriptive term with an image data file containing the digital image.

- 40. The computer-readable medium of claim 43, wherein associating the at least one descriptive term includes:
- generating a file name for the image data file based on the at least one descriptive term indicated by the user.
 - 41. The computer-readable medium of claim 43, wherein associating the at least one descriptive term includes:

linking the at least one descriptive term with the digital image;

25 and

displaying the at least one descriptive term with the digital image, when the digital image is displayed.

42. A computer-readable medium containing instructions for controlling a computer system to perform a method, the computer system having a group of data structures reflecting a logical structure of a data source, the method comprising:

acquiring	а	digital	image;
-----------	---	---------	--------

receiving an audio signal containing at least one descriptive

term;

deriving the at least one descriptive term from the audio signal;

5 and

associating the at least one descriptive term with an image data file containing the digital image.

The computer-readable medium of claim 46, wherein associating the at least one descriptive term includes:

converting the audio signal to a digital audio file; and associating the digital audio file with the image data file containing the digital image.

The computer-readable medium of claim 47, wherein associating the digital audio file includes:

linking the digital audio file with the image data file so that the image data file is recalled when the digital audio file is recalled.

20 45. The computer-readable medium of claim 46, wherein associating the at least one descriptive term includes:

converting the audio signal to a digital audio file;

processing the digital audio file to obtain text comprising at least one word; and

25 associating the text with the image data file.

46. The computer-readable medium of claim 49, wherein associating the text with the image data file includes:

generating a file name for the image data file based on the text.

47. The computer-readable medium of claim 49, wherein associating the text includes:

30

linking the text with the digital image; and displaying the text with the digital image, when the digital image is displayed.

- 5 48. The computer-readable medium of claim 49, wherein processing the digital audio file includes:
 - processing the digital audio file to obtain text comprising at least one candidate word;
- comparing the text to a data base of stored words to obtain at least one descriptive word; and
 - associating the at least one descriptive word with the image data file.
- 49. The computer-readable medium of claim 52, wherein
 associating the at least one descriptive word with the image data file includes:
 generating a file name for the image data file based on the at least one descriptive word.
- 50. The computer-readable medium of claim 52, wherein associating the at least one descriptive word includes:

linking the at least one descriptive word with the digital image; and

displaying the at least one descriptive word with the digital image, when the digital image is displayed.

- 51. The computer-readable medium of claim 52, wherein associating the at least one descriptive word with the image data file includes: displaying a menu containing the at least one descriptive word to
- receiving an indication from the user selecting at least one descriptive term in the menu; and

25

a user;

10

20

25

associating the at least one selected descriptive term with an image data file containing the digital image.

52. A computer-readable medium containing instructions for controlling a computer system to perform a method, the computer system having a group of data structures reflecting a logical structure of a data source, the method comprising:

acquiring a digital image

generating location information representing a geographic location where the digital image was acquired;

associating the location information with an image data file containing the digital image.

53. The computer-readable medium of claim 56, wherein generating location information comprises:

receiving numeric geographic coordinates from a location determination device;

determining at least one alphanumeric location label corresponding to the numeric geographic coordinates; and

associating the at least one alphanumeric location label with the image data file.

54. The computer-readable medium of claim 56, wherein generating location information comprises:

receiving numeric geographic coordinates from a location determination device;

displaying a menu of at least one alphanumeric location label corresponding to points near the location corresponding to the numeric geographic coordinates; and

receiving an input from a user to select at least one of the at least one alphanumeric location label in the menu.

- 55. The computer-readable medium of claim 57, wherein associating the at least one alphanumeric location label with the image data file includes:
- generating a file name for the image data file based on the at least one alphanumeric location label.
 - 56. The computer-readable medium of claim 57, wherein associating the at least one alphanumeric location label with the image data file includes:
- linking the at least alphanumeric location label with the digital image; and
 - displaying the at least one alphanumeric location label with the digital image, when the digital image is displayed.
- 15 57. The computer-readable medium of claim 57, wherein associating the at least one alphanumeric location label with the image data file includes:

displaying the at least one alphanumeric location label to a user; receiving an indication from the user selecting at least one alphanumeric location label in the menu; and

associating the at least one selected alphanumeric location label with an image data file containing the digital image.

20




Fig. 1






Fig. 3








N\$DOCID: <WO__0051342A1_I_>

-1G. 5


FIG. 6












8/8



NSDOCID: <WO___0051342A1_I_>

Form PCT/ISA/210 (second sheet) (July 1998)*



International application No. PCT/US00/05029

Во	x i C	Observations where certain claims were found unsearchable (Continuation of item 1 of first sheet)		
4This international report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:				
1.		Claims Nos.: because they relate to subject matter not required to be searched by this Authority, namely:		
2.		Claims Nos.: because they relate to parts of the international application that do not comply with the prescribed requirements to such an extent that no meaningful international search can be carried out, specifically:		
3.	x	Claims Nos.: 40,41,43,44-49, 53-57 because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).		
Воз	ı II (Observations where unity of invention is lacking (Continuation of item 2 of first sheet)		
Thi	s Inte	rnational Searching Authority found multiple inventions in this international application, as follows:		
1.		As all required additional search fees were timely paid by the applicant, this international search report covers all searchable claims.		
2.		As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.		
3.		As only some of the required additional search fees were timely paid by the applicant, this international search report covers only those claims for which fees were paid, specifically claims Nos.:		
4.		No required additional search fees were timely paid by the applicant. Consequently, this international search report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:		
Re	mark	on Protest		
		No protest accompanied the payment of additional search fees.		

Form PCT/ISA/210 (continuation of first sheet(1)) (July 1998) *

A. CLASSIFICATION OF SUBJECT MATTER: US CL :	
348/207,231,232,233,239; 396/429,310,312; 382/ 100, 306; 704/3, 251,254, 260,276	
: ·	
	-
	1

Form PCT/ISA/210 (extra sheet) (July 1998) #